

13

SUNISO® SL 32
Material Safety Data Sheet

SECTION I - COMPANY IDENTIFICATION

PRODUCT: SUNISO SL 32, Synthetic Polyol Ester Refrigeration Lubricant

CAT. NO.: LSL32*
* - container size

PACKED & DISTRIBUTED BY:

Virginia KMP Corporation
4100 Platinum Way
Dallas, Texas 75237

TELEPHONE NUMBERS:

Office: 1-(214) 330-7731
Emergency Only: 1-(800) 424-9300

SECTION II - INGREDIENTS AND HAZARDOUS INGREDIENTS

OSHA Hazardous Components (29 CFR 1910.1200)

EXPOSURE LIMITS: 8 HR. TWA

OSHA PEL

ACGIH TLV

PROPRIETARY MIXTURE (100%)

NONE

NONE

SECTION III - HAZARDS IDENTIFICATIONS

EMERGENCY OVERVIEW: None known..

POTENTIAL HEALTH EFFECTS:

INHALATION: No toxic effects are expected. High concentrations of mist may be irritating to upper respiratory tract.

EYE CONTACT: Similar products with similar additive packages were not classified as irritants by ocular application.

SKIN CONTACT: Similar products with similar additive packages were not classified as primary irritants or as corrosive materials by dermal application. May aggravate pre-existing skin disorders.

INGESTION: The acute oral LD50 of a similar product was >5.0 g/kg in rats..

CHRONIC Effects: None known

NOTE:

CARCINOGENICITY: LISTED IN NTP? No

IARC? No

OSHA Regulated? No

SECTION IV - FIRST AID MEASURES

INHALATION: Remove victim to fresh air. If a cough or other respiratory symptoms develop, consult a physician.

EYE CONTACT: Immediately flush with plenty of water for 15 minutes. DO NOT rub eyes. If redness, itching, or a burning sensation develops, get medical attention.

SKIN CONTACT: Wash material off of skin with plenty of soap and water. If redness, itching, or burning sensation develops get medical attention. Wash clothes before reuse.

INGESTION: DO NOT INDUCE VOMITING. Give 1 or 2 glasses of water to drink. DO NOT give sodium bicarbonate, fruit juices or vinegar. Never give anything by mouth to a unconscious or having convulsions. If gastrointestinal symptoms develop, consult a physician.

SECTION V - FIRE FIGHTING MEASURES

FLASHPOINT (TEST METHOD): 478 °F, 248 °C (min.)

FLAMMABLE LIMITS: LOWER: NAP

UPPER: NAP

AUTOIGNITION TEMPERATURE: ND

GENERAL HAZARD:

FIRE FIGHTING INSTRUCTIONS: Approach fire from upwind side. Avoid breathing smoke, fumes, mist or vapors on downwind side. Firefighters wear protective clothing and self contained breathing apparatus.

EXTINGUISHING MEDIA: Water fog, foam, carbon dioxide, or dry chemical. Water may be ineffective but should be used to keep containers cool.

HAZARDOUS COMBUSTION PRODUCTS: Smoke and fumes, carbon monoxide, carbon dioxide.

SECTION VI - ACCIDENTAL RELEASE MEASURES

LAND SPILL: Contain spill. Keep out of sewers and drains. Soak up material with absorbent and shovel into a chemical waste container.

WATER SPILL: Notify proper authorities.

Clean up leaks/spills immediately to prevent soil or water contamination.

SECTION VII - HANDLING AND STORAGE

HANDLING: Product is highly hygroscopic. Keep container closed tightly.

STORAGE: Follow normal storage practices. No special storage requirements necessary.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

SUNISO® SL 32

ENGINEERING CONTROLS: Local exhaust ventilation is recommended.

PERSONAL PROTECTION: Use chemical impervious gloves and apron, chemical goggles or full face shield. Respiratory protection is not normally needed under proper conditions of use and storage. Use MSHA - NIOSH approved respirator for organic vapors, dust and mists whose TLV is greater than 0.05 mg/m³.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE @ 20 C: Not determined

SPECIFIC GRAVITY (H₂O=1): 0.980

SOLUBILITY IN WATER: Nil

pH: NAP

BOILING POINT: Not determined

APPEARANCE & ODOR: Clear liquid, slight odor.

VAPOR DENSITY (Air=1): NA

EVAPORATION RATE (H₂O=1): NAP

VOC (LB/GAL): NAP

FREEZING POINT: NA

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: High heat.

MATERIALS TO AVOID: Oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: Not likely.

SECTION XI - TOXICOLOGICAL INFORMATION

From similar product **LD50:** >5000 mg/kg (oral - rat)

SECTION XII - ECOLOGICAL INFORMATION

ND

SECTION XIII - DISPOSAL CONSIDERATIONS

Reclaim where possible. Fuel blending is another possibility. Avoid landfilling of liquids. All recovered material should be packaged, labeled, transported, and disposed or reclaimed in conformance with applicable laws and regulations.

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Not regulated.

HAZARD CLASS: NA

IDENTIFICATION NUMBER: NA

DOT Emergency Guide #: NA

Reportable Quantity (RQ): NA

International: NA

SECTION XV - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act): Components of this product are listed on the TSCA Inventory.

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act): Not listed.

SARA TITLE III (Superfund Amendments and Reauthorization Act): Not listed.

CALIFORNIA PROPOSITION 65: Not listed.

SECTION XVI - OTHER INFORMATION

State Right-to-Know Programs: Not listed.

NFPA Ratings: Unrated.

Health:

Flammability:

Reactivity:

HMIS Protective Equipment:

Prepared by: Virginia KMP Corporation

revised: 12/20/00

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Virginia KMP. The data on this sheet related only to specific material designated herein. Virginia KMP assumes no legal responsibility for use or reliance upon these data.